



Q-STROBE OPERATION MANUAL

Caution! Always disconnect from main power before replacing lamps or servicing unit. Remember to always replace with same lamp and fuse. This product is intended for indoor use only. To prevent fire or shock hazard, do not expose this unit to rain or moisture.

Thank you for purchasing this BOTEX product .For your convenience this product has been lamped and is ready to be used , there is no assembly required . Please read the following instructions before installing or using your new unit.

Product Description:

A new revolution in Strobe Lights! This unit is a 70 W, ultra light weight Strobe Light that combines long tube life with the maximum brightness and reliability. There are two control modes for flash rate , one is internally controlled and the other is externally controlled . In addition , it is a plastic high tech case design with hanging bracket for installing easily.

Product Instructions:

Plug this unit into power. Flash rate may be controlled by the variable speed knob located on back of unit. The unit linkable via 1/4" mono jack, and may be controlled by the BOTEX CN-100,CN-106, and the CN-108. When linking , follow the IN & OUT input on back of unit. The unit may be hung in a safe location by its hanging bracket.

To replace lamp ; unscrew front dome of the fixture. Do not touch lamp with bare fingers , oil from fingers will ruin lamp. Use a clean, dry cloth for replacement. Replace bulbs; reassemble.

For service, contact your BOTEX dealer.

SPECIFICATIONS:

Flash tube :BT-QI 70W, Power: AC 230V~50Hz Weight: 1.3Kg.
Size: 250Wx190Dx250H Fuse(internal): F2A 250V 5x20mm.

